

File E157180  
Project 06CA53659

2007-02-10

REPORT

on

COMPONENT - MOTOR CONTROLLERS, FLOAT- AND PRESSURE-OPERATED - COMPONENT

MA-TER SRL  
PESSANO CON BORNAGO, MI, ITALY

Copyright © 2007 Underwriters Laboratories Inc.®

Underwriters Laboratories Inc. authorizes the above-named company to reproduce this Report provided it is reproduced in its entirety.

Underwriters Laboratories Inc. authorizes the above-named company to reproduce the latest pages of that portion of this Report consisting of this Cover Page through Page 5.

## DESCRIPTION

## PRODUCT COVERED:

USR, CNR - Open Type, Industrial Control Equipment, Component - Float and Pressure Operated Motor Controllers, Pressure Switches,

## "GP6 Series":

- Model No. GP6, followed by 0, followed by 0, 1, 2, 5.
- **Model No. GP61.**

## ENGINEERING CONSIDERATIONS (NOT FOR UL REPRESENTATIVE USE):

- USR - Indicates investigated to United States Standard for Industrial Control Equipment, UL508 (Seventeenth Edition).
- CNR - Indicates investigated to Canadian National Standard for Industrial Control Equipment, C22.2 No.14-05

Note: USR = United States Standards - Recognized  
CNR = Canadian National Standards - Certified

## GENERAL:

The devices covered by this Report are pressure-operated single-pole switches intended for the direct command of single-phase circuit, indicated for use in steam generators and any pressure control systems, at a maximum operating ambient temperature of 85°C. This device has been subjected to 6,000 cycles of operation and it is intended for regulating use only. The pressure connection is made through an in-let 1/4 inch or 1/8 inch male thread (ISO7 or ISO228 or NPT) connector, or through an in-let "Rapid-coupling" connector, provided on the housing-base of the device.

Since these devices are intended for use in steam generators and any pressure control systems, their actuation consists of a slow increase in the applied pressure until the actuating "off" pressure is reached. The "off" pressure is adjustable, in the pressure range, acting on the regulation screw.

The contact will close if the applied pressure slow decrease under the "on" reset pressure value  $P_{on} = P_{off} - P_{diff}$ .

## RATINGS:

## 1. Electrical Ratings -

Pressure Switch Model Nos.	Electrical Ratings (related to Micro-Switch ratings)
"GP6 Series"	8 A 125 / 250 Vac (6,000 cycles)

**Apart the model GP61 which is maximum rated 1A 125 / 250 Vac (6000 cycles).**

## 2. Environmental Ratings -

- Operating Ambient Temperature - 85°C max

## 3. Operating Pressure Ratings -

3a) Operating Pressure Range: 0.05 ÷ 6.0 Bars (0.7 ÷ 87.0 PSI)

3b) Fixed Differential Pressure: 0.6 Bars (8.7 PSI)

3c) Maximum Pressure: **6.0 Bars (87.0 PSI)**

## 4) Threaded Connector - Hydraulic-Nipple / "Tightening Torque" Ratings:

a) Polymeric Nipple - 0.5 Nm (0.05 Kg m)

b) Metal Nipple / Metal Adapter - 8.8 Nm (0.90 Kg m)

Refer to Ills. 1 for details.

## NOMENCLATURE BREAKDOWN:

Model No.:	<u>GP6</u>	<u>0</u>	<u>0</u>
	I	II	III

I. Basic Pressure Switch Series, GP6

II. Variations for End-use Applications

0 = Basic Pressure Switch model **1 = Connected by connector type Rast 2,5 model.**

III. Switch Housing Base Materials (**only for models GP60x**)

- 0 = Housing metal part constructed of Brass
- 1 = Housing metal part constructed of Stainless Steel
- 2 = Housing polymeric part constructed of R/C Plastic (QMFZ2)
- 5 = Brass / Polymeric Housing Base provided with an in-let "Rapid-coupling" connector